





	Ayleen	100	200	300	400
Chassis					
Caster covering with roller locking per axle		x	•	x	x
Foot with electronic caster positioning		•	x	x	x
4-wheel central brake with straight run function		x	x	•	o
50 mm rubberised double caster		•	•	x	x
100 mm double caster		x	x	•	•
125 mm caster		x	x	o	o
Comfort characteristics					
Auto-contour		x	•	•	•
Side rail					
Full length side rail		•	•	•	•
One-side split side rail		o	o	o	o
Mobilising side rail system		o	o	o	o
Extension possibilities					
Integrated bed extension		o	o	o	o
Bedding storage (only in conjunction with integr. bed extension)		o	o	o	o
Mattress base					
Slatted bed base		o	o	o	o
Metal rail		•	•	•	•
Comfort		o	o	o	o
ABS		o	o	o	o
Technical details					
Working position		78 cm	78 cm	75 cm	80 cm
Transfer position		38 cm	38 cm	35 cm	40 cm
Safe working load		180 kg	180 kg	180 kg	180 kg
External dimensions		100 x 206 cm	100 x 206 cm	100 x 206 cm	100 x 206 cm
Mattress base		90 x 200 cm	90 x 200 cm	90 x 200 cm	90 x 200 cm
Adjustment functions					

• as standard o optional x not available



SAFETY IN THE AYLEEN SERIES

EC Medical Device Directive
93/42 EEC

Adjustable care beds
DIN EN 1970 / DIN EN 60601-2-52:2010

Medical electrical equipment
DIN EN 60601-1

Electromagnetic compatibility
DIN EN 60601-1-2