





Impulse	400	400 LR100	Ambiente	XL
Chassis				
Caster covering with roller locking per axle	•	x	x	x
Foot with electronic caster positioning	x	x	•	x
4-wheel central brake with straight run function	x	•	x	•
50 mm rubberised double caster	•	x	•	x
100 mm double caster	x	•	x	•
125 mm caster	x	◦	x	◦
Comfort characteristics				
Comfort seat	•	•	•	◦
Auto-contour	•	•	•	•
Mobilisation				
Transfer position	•	•	x	x
Trendelenburg /Anti-Trendelenburg positioning	•	•	•	◦
Side rail				
Full length side rail	•	•	•	x
One-side split side rail	◦	◦	◦	x
Mobilising side rail system	◦	◦	◦	•
Safety				
Low-level care bed – Fall prevention	•	•	x	x
Extension possibilities				
Integrated bed extension	◦	◦	◦	x
Bedding storage (only in conjunction with integr. bed extension)	◦	◦	◦	x
Mattress base				
Slatted bed base	◦	◦	◦	x
Metal rail	•	•	•	•
Comfort	◦	◦	◦	x
ABS	◦	◦	◦	x
Technical data				
Working position	82 cm	82 cm	84 cm	83 cm
Low position	25 cm	26 cm	37 cm	33 cm
Safe working load	225 kg	225 kg	225 kg	300 kg
External dimensions	100 x 206 cm	100 x 206 cm	100 x 206 cm	110 x 206 cm
Mattress base	90 x 200 cm	90 x 200 cm	90 x 200 cm	100 x 200 cm
Adjustment functions				

• as standard ◦ optional x not available



SAFETY IN THE IMPULSE SERIES

EC Medical Device Directive
93/42 EEC

Adjustable care beds
DIN EN 1970 / DIN EN 60601-2-52:2010

Medical electrical equipment
DIN EN 60601-1

Electromagnetic compatibility
DIN EN 60601-1-2